

MASTER LEDtube HF T8 - 1500 mm

Ballast Compatibility



KEY

	Ballast is compatible
*	Ballast is compatible, light output may differ >10% compared to specifications
Dim	Ballast is compatible and conditional released for dimming
CF	Ballast is compatible and supports camera friendly performance on commonly used consumer cameras
	Ballast is not compatible
	Ballast LEDtube combination not tested

This document is for information purposes and must be treated as recommendation. Signify attempted to provide best results, results are generated in lab controlled environment and may differ from actual application conditions



	Ballast type	10nc / Ref. no.	Lamps on ballast	MAS LEDtube HF 1500mm HO 20W8xx T8	MAS LEDtube HF 1500mm UO 24W8xx T8	
				Model number / EOC code: 9290035537 / 871951446694400 9290035538 / 871951446690600 9290035539 / 871951446692000	Model number / EOC code: 9290035543 / 871951446706400 9290035544 / 871951446702600 9290035545 / 871951446704000	
				AC (50 Hz) on HF Ballast Compatible	AC (50 Hz) on HF Ballast Compatible	
PHILIPS	EI 158 TL-D 220-240	9137 006 075	1		*	
	HF-B 158 TLD 220-240	9137 001 123	1		*	
	HF-B 158 TLD EII 220-240	9137 001 927	1	*	*	
	HF-B 258 TLD 220-240	9137 001 125	2	*	*	
	HF-B 258 TL-D EII 220-240	9137 001 929	2	* / CF	* / CF	
	HF-E 158 TL-D	9137 130 389	1			
	HF-E 1/2 58 TL-D II	9137 130 409	2			
	HF-E 1/2 58 TL-D II	9137 130 409	1	* / CF	* / CF	
	HF-F 154/155 TL5 HO/PL-L III IDC	9137 130 282	1	CF	CF	
	HF-F 158 TLD 230-240	9137001111	1	CF	CF	
	HF-F 158 TLD EII 220-240	9137 001 912	1	*	*	
	HF-F 158 TL-D III IDC	9137 130 318	1	CF	CF	
	HF-F 258 TLD EII 220-240	9137 001 916	2	* / CF	* / CF	
	HF-F 258 TL-D III IDC	9137 130 319	2			
	HF-F Xt 158 TLD EII 220-240	9137 006 179	1	* / CF	* / CF	
	HF-F Xt 258 TL-D EII 220-240	9137 006 180	2	* / CF	* / CF	
	HF-F 158 TLD 220-240	9137 001 185	1			
	HF-F 258 TLD 230-240	9137 001 110	2	*	*	
	HF-R 258 TLD 220-240	9137 001 119	2	*	*	
	HF-R 158 TLD EII	9137 006 094	1	Dim / CF	Dim / CF	
	HF-R 258 TLD EII	9137 006 095	2			
	HF-RITD 1 28/35/49/54TL5	9137006956	1			
	HF-RITD 2 28/35/49/54TL5	9137006958	2			
	HF-S 158 (Designed for Philips Luminaires)		1	*	*	
	HF-S 158 TL-D II	9137 130 322	1	CF	CF	
	HF-S 258 TL-D II	9137 130 325	2	CF	CF	
	HF-S 258 TL-D II HT	9137 006 899	2	CF	CF	
	HF-S 158 TLD 220-240	9137 006 319	1	CF	CF	
	EB-P 258 TLD ICC 220-240	9137 130 210	2	* / CF	* / CF	
	HF-P 258 TLD 220-240	9137001206	2			
	HF-S 258 TLD 220-240	9137006452	2	CF	CF	
	OSRAM	QT DeLuxe HF 1x58 230-240 DIM		1		
		QT DeLuxe HF 2x58 230-240 Dim		2		
QT-FIT8 1x58-70			1	CF	CF	
QT-FIT8 2x58-70			2			
QTP8 1x58			1	* / CF	* / CF	
QTP8 2x58			2	*	*	
QTP 2x58/230-240			2	* / CF	* / CF	
QTP 1x58/230-240			1			
QTP-OPTIMAL 1x54-58			1	CF	CF	
QTP-OPTIMAL 2x54-58			2	CF	CF	
QT 1x58 DIM			1			
HELIAR	EL1x58ngn		1			
	EL1x58s		1	CF	CF	
	EL2x58es		2	*	*	
	EL2x58HF		2	CF	CF	
	EL2x58ngn		2			
TRIDONIC ATCO	EL2x58s		2	CF	CF	
	PC 1/58 T8 INDUSTRY	86 458 037	1	* / CF	* / CF	
	PC 1/58 T8 PRO	22 176 094	1	* / CF	* / CF	
	PC 1/58 T8 PRO	22 176 007	1	* / CF	* / CF	
	PC 1x58 T8 PRO Ip	22 185 215	1	CF	CF	
	PC 2/58 T8 INDUSTRY	86 458 038	2	* / CF	* / CF	
	PC 2x58 E011		2			
	PC 2x58 E011 IDC	22 083 174	2			
	PC 2x58 T8 PRO sl	22 185 218	2	* / CF	* / CF	
	PC 1x58 T8 TOP sl	22185224	1	CF	CF	
	PC 2x58 T8 TOP sl	22185227	2	* / CF	* / CF	
	PCA 1/58 excel one4all	22 085 286	1			
	PCA 2x58 EXCEL One4all Ip	28 000 040	2			

