

Description

An overview of Trailing-edge dimmers that are tested with the L05021 MINIDIM Driver.

Dimmerlist

Manufacturer	Dimmer	Note	Minimum LED-Load	Minimum Dim-range	Stability
BERKER	286710	(same as Insta 51190)	2.5 Watt	20%	OK
BERKER	-	(same as Insta 53128 R)	-	25%	NOT STABLE
BUSCH J	6513U-102		7.5 Watt	20%	OK
ELARI	ATD 315		2.5 Watt	20%	OK
ELARI	ATD 600R		7.5 Watt	20%	OK
EPV	PAB 315		2.5 Watt	20%	OK
GIRA	-	(same as Insta 51190)	2.5 Watt	20%	OK
GIRA	-	(same as Insta 53128 R)	-	25%	NOT STABLE
INSTA	51190		2.5 Watt	20%	OK
INSTA	53128 R		-	25%	NOT STABLE
INSTA	FUNK 576650 22		10 Watt	30%	OK
INSTA	51040		2.5 Watt	20%	OK
JUNG	1254 UDE	(same as Insta 53128 R)	-	25%	NOT STABLE
JUNG	225TDE		2.5 Watt	20%	OK
LUTRON	LPRPM-4A		2.5 Watt	15%	OK
LUTRON	GRAFIK INTEGRAL GXI		2.5 Watt	15%	OK
OPUS	852395		2.5 Watt	30%	OK
PEHA	433HAB		2.5 Watt	20%	OK
SCHNEIDER	ATD 315		2.5 Watt	20%	OK
SCHNEIDER	600R		7.5 Watt	20%	OK
SIEMENS	5 TC8 284		7.5 Watt	15%	OK

